



SLIDE-A-MATIC XL (Extra Long) SPECIFICATIONS, SIZES AND CONSTRUCTION

Slide-A-Matic XL guarding is a revised version of our standard Slide-A-Matic gate, however, it has no limitations on the number of panels that can be used, dramatically extending gate lengths. It has been intricately engineered to open and close effortlessly and to rotate to the side in order to provide complete access to an area. There is now a short-span double caster on each panel.

SPECIFICATIONS

General Dimensions Standard 76-in. Tall Gates (Inches)

Single Panel Width	51.50
Panel Height	72.25
Anchor and Latch Post Height	76.65
Gap between Latch Post and Gate	2.25
Gap between Anchor Post and Gate	4.00
Gap between bottom of gate and floor	4.40
Total height from floor to top of gate	76.65
Rotation	252 degrees

General Dimensions Std. 48 & 42-in. Short Gates (Inches)

Single Panel Width	51.50
Panel Height 48-in. Gate	43.62
Panel Height 42-in. Gate	37.62
Anchor and Latch Post Height	42.00
Gap between Latch Post and Gate	2.25
Gap between Anchor Post and Gate	4.0
Gap between bottom of gate and floor	4.40
Total height from floor to top of 48-in. gate	48.00
Total height from floor to top of 42-in. gate	42.00
Rotation	252 degrees

Gate Widths Extended

2-Panel Gate	94.00
For each additional panel add	42.50
Panel overlap	9.00

Gate Widths Retracted

2-Panel Gate	55.50
For each additional panel add	4.00
Panel protrusion (ea. panel)	4.00

Gate Thickness (When retracted)

2-Panel Gate	1.88
For each additional panel add	1.00



4-Panel Short Slide-A-Matic with yellow, 2-inch welded wire inserts. Total gate height from floor is 4.40 inches.



3-Panel Slide-A-Matic with black welded wire inserts. Note custom, factory installed interlock device.

GATE CONSTRUCTION

Anchor and Latch Post

- Posts are 2-inch square tube, capped, with .1875 wall.
- Foot plate is 6" x 6" x .75" CRS with four .562" drilled holes.

Vertical Slide Latch

.75-inch hardened steel, pad-lockable. Latch can be operated from either side of the gate.

Casters

- 2.5-inch swivel, non-marking. 175 lb. capacity each.
- Number of caster sets is equal to the number of gate panels.

Wire Inserts

- .120 welded wire on 2-in. centers (square).
- Expanded Metal, 1/2 #20 Flattened, 65% Open Area.
- Expanded Metal, 1/2 #18 Flattened, 65% Open Area.

Color (Premium Powdercoat)

- Safety Yellow Standard. Also available with black inserts.
- Other colors available. Inquire.

Installation Instructions

"Step-by-step" installation drawings are supplied relevant to each purchase configuration. Installation is quick and easy.

Warranty

The Slide-A-Matic warranty is for a period of 1-year and covers replacement of any defective parts. Labor is not included.

